A LENS OPTICAL COUPLER

BACKGROUND

The invention pertains to optical couplers and particularly

5   to couplers used for conveying laser light from a source into an

optical fiber.

Several patent documents may be related to optical coupling

between optoelectronic elements and optical media. They include

U.S. Patent No. 6,086, 263 by Selli et al., issued July 11,

10   2000, entitled "Active Device Receptacle" and owned by the

assignee of the present application; U.S. Patent No. 6,302,596

B1 by Cohen et al., issued October 16, 2001, and entitled "Small

Form Factor Optoelectronic Receivers"; U.S. Patent No. 5,692,083

by Bennet, issued November 25, 1997, and entitled "In-Line

15   Unitary Optical Device Mount and Package therefore"; and U.S.

Patent 6,536,959 B2, by Kuhn et al., issued March 25, 2003, and

entitled "Coupling Configuration for Connecting an Optical Fiber

to an Optoelectronic Component"; which are herein incorporated

by reference.

20   Coupling efficiency between light sources and optical media

is an important factor in various communications and other

applications. Coupling efficiency, for instance, from a laser

source to a single mode fiber not only is affected by a mismatch

between the laser field/fiber-mode but also by aberrations in

the coupling optics. A single ball lens may be used for single

mode fiber coupling, but because of the spherical aberration

5   from the ball lens, the coupling efficiency may be only about

fifty percent. However, many communications applications need

higher coupling efficiencies because of distance, weak light

sources and high data rates. An aspherical glass lens is able

to achieve high fiber coupling but its cost may be too high for

10   practical use.

SUMMARY

The present invention is a low cost, highly efficient

system for coupling light from a light source into optical

15   fiber. Among other features, it may have a spherical lens and

an aspherical lens situated on the same optical path.

BRIEF DESCRIPTION OF THE DRAWING

Figure 1 is a diagram of an optical system with only a ball

20   lens;

Figure 2 shows an optical system with a convex aspherical

design;

2

Figure 3 shows an optical system with an alternative convex aspherical design;

Figure 4 shows an optical coupling system with a concave aspherical design;

5   Figure 5 is a graph of coupling efficiency versus deviation of the output relative to the optical fiber of the system of Figure 4;

Figure 6 is a graph of the coupling efficiency of the system versus it temperature; and

10   Figure 7 is a graph of the ray aberrations of the system of Figure 4.

DESCRIPTION

Figure 1 shows a system 30 for coupling a light source 32

15   to an optical fiber 33. System 30 may have only one lens 35 which is a glass ball lens. Light 31 may propagate from source 32 through window 34 and lens 35. From lens 35 is spherically focused light 37 of which may match the fiber mode and couple into the end of fiber 33. The other spherically focused light

20   38 from lens 35 may mismatch the fiber mode and miss the end of fiber 33 and therefore will not be coupled into the fiber 33.

Source 32 of Figure 1 may be about 381 microns (15 mils) from the closer surface of window 34. One may note that if a flip chip is used, window 34 may be spaced such that it is in intimate contact or nearly so with source 32. Window 34 may be

5   about 203 microns (8 mils) thick. Window 34 may be about 264 microns (10.4 mils) from lens 35. Lens 35 may have a diameter of about 1.5 millimeters (59 mils). The distance from lens 35 may be about 1.212 millimeters (47.7 mils) from the end of fiber 33. The above-noted length measurements are along an optical

10 axis 18.

Figure 2 reveals an illustrative example of the invention. Coupler system 10 may be a two-lens device used for coupling light 11 from a light source such as, for example, a vertical cavity surface emitting laser (VCSEL) 12, into a single mode

15 (SM) optical fiber 13. Light 11 may propagate through a spherical ball lens 15. Light 17 may exit lens 15 and be focused on an end of a fiber 13 like that of light 37 of Figure 1. However, because of the spherical aberration from the ball lens, light 19 might not be focused on the end of fiber 13 along

20 with light 17 in the same manner as light 38 is not focused along with light 37 on the end of fiber 33 in Figure 1. Light 17 and 19 in Figure 2 may enter an aspherical lens 16. Lens 16

4

may be shaped in a non-spherical way to focus light 17 and 19 on to the end of fiber 13 at the same time. A similar arrangement and principle of focusing may appear in coupling systems 20 and 40 of Figures 4 and 3, respectively.

5   VCSEL 12 may be a single mode source. Light 11 may propagate through a protective window 14 of a (hermetically) sealed package containing the VCSEL onto a ball lens 15. The distance between VCSEL 12 and the surface of window 14 closer to VCSEL 12 may be about 380 microns (15 mils). Window 14 may be

10   about 203 microns (8 mils) thick and consist of BK7^{TM}, Corning #7052, or any suitable transmissive material. The distance between the surface of the window 14 (closer to lens 15) and lens 15 may be about 280 microns (11 mils) along the optical axis. Spherical lens 15 may be about 1.5 millimeters (59 mils)

15   in diameter. Lens 25 may be a glass ball lens. It may be composed of BK7^{TM}, LaSFN9, or any suitable material. Light 11 may move through lens 15 and out of it into an aspherical lens 16. The distance between lens 15 and lens 16 may be about 561 microns (22.1 mils). Light 11 may propagate through lens 16

20   into optical fiber 13. The end of fiber 13 may be in physical contact with lens 16 but not required to be so. The length of lens 16 may be about 209 microns (82.3 mils). The above-noted

length measurements are along the optical axis. Lens 16 may be a convex lens made from Zeonex™ E48R available from Zeon Chemicals L.P., 4111 Bells Lane, Louisville, KY 40211. The lens may also be made from GE ULTEM. A 1.5 mm ball lens 15 of BK7™

5   material may be available from Edmund Industrial Optics, 101 East Gloucester Pike, Barrington, NJ 08007-1380. Optical fiber 13 may be an SMF-28™ single mode optical fiber available from Corning Incorporated, One Riverfront Plaza, Corning, NY 14831. One may note that the dimensions illustrated above are typical

10   and other geometries may be functional as well.

    The present optical coupler may have both high coupling efficiency and low cost. The coupling optics may use a glass ball lens and a molded aspherical lens. The aberration of the ball lens may degrade the efficiency of the coupling system.

15   However, the ball lens' spherical aberration may be compensated by the light ray directing properties of the aspherical plastic lens. Since the ball lens may have significantly more optical power than the plastic lens in the coupling system, the plastic lens' poor thermal properties may be compensated for and

20   minimized. Therefore, an appropriately designed combination of a glass ball lens and plastic molded aspherical lens may provide a thermally stable and highly efficient optical coupling system.

Lens 16 may be composed of glass or be a single aspherical

glass lens. Glass aspherical lenses may have good thermal

properties and less aberration than a ball lens. They may be

somewhat expensive and difficult to produce. Plastic aspherical

5   lenses may be easily and inexpensively producible; however, they

do not have thermal properties as good as the glass lenses. Yet

the plastic aspherical lenses have much less aberration than the

ball lenses. For instance, light rays coming from a spherical

lens periphery may form an image before the ideal focal point.

10   For this reason, the spherical aberration (a blurred image) may

occur at the center portion of the image formed. Or if the

focus is readjusted for the center portion of the image, then

the spherical aberration (again, a blurred image) may occur at

the periphery of the image. In other words, it may not be

15   possible for all of the parallel rays going through a spherical

lens to converge at one point. An awkward and cumbersome

multitude of spherical lenses might be designed to partially

correct this aberration problem. However, one aspherical lens

may be designed to gather or converge all of the parallel rays

20   of light to one focal point. The aspherical lens may have

surface with a specially designed curvature to achieve this

convergence of the light rays. The aspherical lens surface does

not completely conform to the shape of a sphere like that of a
spherical lens. Mass production technologies including plastic
mold technology may be used to mold aspherical lenses by pouring
or injecting plastic material into a rather precise aspherical

5 mold. Further, the aspherical lens may achieve a coupling
efficiency into a single mode fiber above ninety percent for
coupling systems 10, 20 and 40. This is a desired performance
feature for VCSEL communication applications since VCSEL optical
power is relatively low compared to other laser sources.

10 Significant power is better conveyed with a glass aspherical
lens; however, the cost of a glass aspherical lens is high
(i.e., greater than eight dollars per lens in year 2000 with
high volume pricing). The inexpensive (i.e., less than a dollar
with high volume pricing) aspherical lens may be the poured or

15 injection molded plastic lens. The aspherical lens may be made
of another material similar to plastic. The plastic lens may
have poor thermal characteristics but a glass ball lens may
compensate for those characteristics in a coupling system with
the plastic lens. The ball lens may be made of another material

20 similar to glass.

A design for the aspherical convex lens 16 may be indicated
by the following equation and parameter values.

8

$$z=\{cr^2/[1+(1-(1+k)c^2r^2)^{1/2}]\}+A_6r^6+A_8r^8$$

Surface 1

c=1/R; R=1.457374 (Unit: mm)

k=-18.455693

5   A_6=-24.768767

A_8=-20.028863

Illustrative examples of the invention have an optical

design which may possess both high coupling efficiency and low

cost.   The spherical aberration of ball lens 15 may be

10   compensated for by aspherical plastic lens 16.   Because ball

lens 15 may convey the most optical power in system 10, the

combination of a glass ball lens and plastic molded optics may

provide thermal stability and high coupling efficiency for

optoelectronic element and single mode optical fiber coupling

15   applications.

Figure 3 is a layout of an optical coupler system 40 having

a convex aspherical lens 46 that may have a different design

than that of convex aspherical lens 16 of system 10.   Similarly,

light source 42 may emit a light 41 that goes through a

20   hermetically sealed window of the package wherein light source

42 is situated.   Light 41 may go through a ball lens 45 and

convex aspherical lens 46.   The light from lens 46 may enter

9

fiber 43. Components 42, 45, 46 and 43 may be situated on an optical axis 18. Aspherical lens 46 may be a plastic lens. The materials of the components and the dimensions may be similar those of system 10.

5   Figure 4 reveals another illustrative example of the invention. Coupler system 20 may be a two-lens device for coupling light from a single mode (SM) VCSEL 22 into an SM optical fiber 23. The wavelength of the laser light from VCSEL 22 may be 1310 nm. Light 21 may propagate through a protective

10   window 24 into a ball lens 25. VCSEL 22 may be about 381 microns (15 mils) from the closer surface of window 24. Window 24 may be about 203 microns (8 mils) thick. The surface of window 24 closer to lens 25 may be about 305 microns (12 mils) from lens 25. Lens 25 may have a diameter of about 1.5

15   millimeters (59 mils). It may be a glass ball lens. Light 21 may propagate through lens 25 and out of it into an aspherical lens 26. The distance between lens 25 and lens 26 may be about 76 microns (3 mils). Light 21 may propagate through lens 26 into optical fiber 23. Optical fiber 23 has an end that may be

20   in contact with lens 26. The length of lens 26 may be about 205.7 microns (81 mils). The above-noted length measurements may be along the optical axis. The dimensions may be

illustrative examples and may be of other appropriate

magnitudes. Lens 26 may be a concave Zeonex™ E48R (or any other

suitable plastic material) lens. However, lens 26 could be

composed of glass, but because of the high cost (as noted above)

5   of glass aspherical lenses, lens 26 may be a poured or an

injected molded plastic lens.

Lens 25 may be a 1.5 mm ball lens made of LaSFN9™ material

available from Edmund Industrial Optics. Lens 26 may be made of

Zeonex™ E48R material available from Zeon Chemicals L.P. Fiber

10   23 may be an SMF-28™ single mode optical fiber available from

Corning Incorporated. Window 24 may be made from BK7™ material

available from various vendors. Window 24 may be a hermetically

sealed window of a TO-56 can or other package incorporating

light source 22 such as a VCSEL.

15   Like system 10, coupler system 20 may have thermal

stability and high coupling efficiency for coupling light into

SM (single mode) optical fiber 23. In the above-described

systems 10, 20 and 40, end faces of optical fibers 13, 23 and

43, respectively, may be situated so as to be in contact with

20   aspherical lenses 16, 26 and 46, as shown in the respective

Figures 2-4, or the end faces of fibers 13, 23 and 43 may be

situated at distance from lenses 16, 26 and 46, respectively

11

(not shown). Also, the order of ball lenses 15, 25 and 45 and of aspherical lenses 16, 26 and 46 along optical axis 18 may be different than that as shown. The systems disclosed here may be operated with a light source having a wavelength of about 1310

5   nm but may be at another wavelength, such as 850 nm or 1550 nm as well as other wavelengths. The light source may be replaced with a detector and the source of light may be from the optical medium or fiber.

In systems 10, 20 and 40, light sources 12, 22 and 42 may

10   be single mode VCSELs or other sources of that mode. However, they may be multimode VCSELs or other sources of that mode. The optical fibers 13, 23 and 43 of these systems may be single mode or multimode, as applicable.

A design for aspherical concave lens 26 may be indicated by

15   the following equation and parameter values.

$z=\{cr^2/[1+(1-(1+k)c^2r^2)^{1/2}]\}+A_2r^2+A_4r^4$

Surface 1

$c=1/R$; $R=-1.576039$ (Unit: mm)

$k=33.774232$

20   $A_2=0.018687$

$A_4=-2.347015$

The following chart shows the coupling efficiency of system

20 versus deviation of the alignment of the output of the system

with optical fiber 23. This chart appears to reveal system 20

as having a good tolerance to some misalignment of its output

5   with optical fiber 23 to which system 20 is coupling light from

light source 22.

		Coupling Efficiency				
YDE:	.00000	.00100	.00200	.00300	.00400	.00500
XDE						
.00000	.96566	.90779	.77890	.61595	.41840	.26323
.00100	.90779	.85319	.73169	.57822	.39225	.24636
.00200	.77890	.73169	.62675	.49452	.33446	.20926
.00300	.61595	.57822	.49452	.38938	.26231	.16329
.00400	.41840	.39225	.33446	.26231	.17535	.10808
.00500	.26323	.24636	.20926	.16329	.10808	.06577

Figure 5 is a graph that charts coupling efficiency of the

present coupling system 20 versus deviation of the alignment of

10   the output of the system with the optical fiber 23 with the use

of ray-based tracing. The y-axis or ordinate axis indicates the

coupling efficiency from 0 to 1.0 or 100 percent. An x-axis or

abscissa axis indicates the horizontal or x-direction deviation

of the core center of fiber 23 from 0 to 5 microns relative to

15   optical axis 18. Each graph line represents a vertical or y-

direction deviation of the core center of fiber 23 from optical

axis 18. Lines 50, 51, 52, 53, 54 and 55 represent a y-

direction or vertical deviation of 0, 1, 2, 3, 4 and 5 microns,
respectively, of the core center of fiber 23 relative to optical
axis 18.

5 Figure 6 is a graph of the coupling efficiency of system 20
versus it package soak temperature from -45 to 100 degrees
Centigrade (-49 to 212 degrees F.) as shown by line 60. This
graph may demonstrate the thermal stability of system 20.
System 10 may be regarded to have similar coupling efficiencies
under conditions like those of system 20.

10 Figure 7 graphs the aberrations of the across the output
face of system 20 in an x-axis direction and a y-axis direction.
This graph appears to reveal system 20 to have a rather
distortion free output.

Coupler systems 10, 20, 30 and 40 may be a part of an array
15 of light sources such as VCSELs and an array of fibers to which
that the light is coupled. On the other hand, components 12,
22, 32 and 42 may be detectors receiving light from their
respective coupling systems that are receiving light from an
optical fiber or fibers. The coupled light may include light
20 signals such as communications signals.

Although the invention has been described with respect to
at least one illustrative embodiment, many variations and

14

modifications will become apparent to those skilled in the art upon reading the present specification. It is therefore the intention that the appended claims be interpreted as broadly as possible in view of the prior art to include all such variations and modifications.